

# Vehicle Window Stickers

Clear Polyester - Removable

*Parking stickers are important to identify vehicles authorized to park in certain patrolled parking areas. They also are an ideal way to promote a company's logo or message. These stickers must be visible and oftentimes able to display a handwritten identification. Excellent image quality must be maintained until the sticker expires. The adhesive must bond well to auto glass and bumpers and be easy to apply. Parking stickers provide an additional means of promoting your image.*

#### *End-Use Applications:*

*Parking Stickers  
Oil Change Stickers  
College/Alumni Decals  
After-market Decals*

*For more information on FLEXcon's pressure-sensitive film solutions for Vehicle Window Stickers, contact your local Sales Representative or our Product Branding Business Team at (508) 885-8370.*

*Product ID #: FLX000038*



Product: **FLEXmark® PM 200 Clear PTP  
V-327 400 Poly H-9**

#### Benefits:

- 2.0 mil print-treated clear polyester provides ease of installation
- Ideal for "clear-on-clear" look for viewing reverse-printed graphics through the liner
- Printable via UV and solvent screen
- Low tack, removable pressure-sensitive adhesive is clear and bonds well to smooth glass surfaces while removing cleanly
- Backed with a 4.0 mil clear polyester release liner ideal for manual dispensing
- Polyester release liner provides an excellent diecutting base
- Allows for viewing of reverse-printed graphics through the liner



## FLEXmark® PM 200 Clear PTP V-327 400 Poly H-9

PRODUCT DATA	VALUE	TEST METHOD
<b>Physical Properties</b>		
Thickness (Mils[microns])	Film	2.0 (51) +/- 10%
	Adhesive	0.8-0.9 (20-23) +/- 0.1 (3)
	Liner	4.0 (102) +/- 5%
Dimensional Stability (%)	No Shrinkage Observed	ASTM D 3652 (Modified for use with non-tape products)  Applied Shrinkage: 24 hour dwell time on aluminum panel then 24 hours at 160°F (71°C)
<b>Adhesion Properties</b>		
Ultimate Peel from	Average	ASTM D 903 (Modified for 72 hour dwell time)
	Oz/In (N/m)	
Auto Glass	1 (11)	
Glass	1 (11)	
Tack (gm/sq cm)	230	ASTM D 2979
Expected Exterior Life	Two years (outdoor durability)	
	One year (clean removability)	
Service Temperature Range	-20°F to 302°F (-29°C to 150°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years when stored at 70°F (21°C) and 50% relative humidity	

### Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.

Last Modified On: 10/20/2022

