Transfer Tape

Single Liner

Pressure-sensitive transfer tape adhesives are the ideal solution for mounting and bonding because they transfer easily and bond well to many challenging surfaces.

Markets Include:
Aerospace
Appliance
Automotive
Consumer Electronics
Durable Goods
Heavy Equipment
Industrial Equipment
Rail

Applications Include:
Nameplate/ Brand ID
Overlay
Decal
Sealing gaskets
Gap filling
Surface protection
Grip, traction and anti-slip
Noise and vibration control
Bonding films to replace rivets and welds

For more information on FLEXcon's pressure-sensitive film solutions for Transfer Tapes, contact your local Sales Representative or our Performance Products Business Team at (508) 885-8440.

Product ID #: FLX000492

Product: FLEXcon® FLEXmount® TT 400 V-344 60 LA PFW

Benefits:

- Permanent acrylic adhesive offers high shear and excellent adhesion to metals, and high-surface energy plastics
- Backed with a 60 lb. bleached white kraft liner, polycoated and release coated on two sides
- Release liner has excellent moisture stability and is a good base for rotary, flatbed and steel rule diecutting
- Product is ideal for rough, uneven and textured surface applications

FLEXcon 1 FLEXcon Industrial Park, Spencer, MA 01562-2642, Telephone (508) 885-8440 FAX (508) 885-8355 www.FLEXcon.com

FLEXcon® FLEXmount® TT 400 V-344 60 LA PFW

PRODUCT DATA	VALUE		TEST METHOD
Physical Properties			
Thickness (Mils[microns])	Adhesive	3.9-4.1 (99-104) +/- 0.1 (3)	ASTM D 3652 (Modified for use with non-tape products)
	Liner	4.3 (109) +/- 10%	
Expected Shear			ASTM D 3654 Method A a. 1 hr. dwell b. 1 sq. in. surface c. 4 lb. load
Room Temp (hours)	15		
Tack (gm/sq cm)	910		ASTM D 2979
Expected Exterior Life	Dependant on life of substrate - suitable for outdoor use		
Service Temperature Range	-40ºF to 302ºF (-40ºC to 150ºC)		
Minimum Application Temperature	50ºF (10ºC)		
Storage Stability	Two years when stored at 70ºF (21ºC) and 50% relative humidity		

For the Complete Product Data View: FLEXmount® L-344/V-344 Adhesive Series Data Sheet

Product Performance and Suitability
All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.
Last Modified On: 02/06/2024

FLEXcon 1 FLEXcon Industrial Park, Spencer, MA 01562-2642, Telephone (508) 885-8440 FAX (508) 885-8355 www.FLEXcon.com