

Bumper Stickers - Removable

White Vinyl - Sheet Form

Bumper stickers are most often utilized by businesses for promotional purposes or by individuals to express a point-of-view or cause. They're like "mini-billboards", working 24/7 to get important messages across. Radio station promotions, association memberships, political messages, school and event promotions and novelties are typical applications. Naturally, pressure-sensitive film is a perfect solution because it is highly durable and easy to apply. And it offers a wide variety of options from simple, brilliant white, to eye-catching holographic patterns for interesting light diffraction effects. Bumper stickers are an effective, yet inexpensive way to get across your message. For more information on FLEXcon's pressure-sensitive film solutions for bumper stickers, contact your local Sales Representative or our Performance Products Business Team at (508) 885-8440.

Product ID #: FLX007127



Product:

Classics Plus® 41076

Benefits:

- 3.5 mil flexible white vinyl film provides durability and easy installation
- Printable via UV and solvent screen. Please test for ink adhesion with your specific ink chemistry
- Removable pressure-sensitive acrylic adhesive resists oozing and reduces adhesive build-up, for ease of diecutting
- Adheres to a variety of surfaces, including chrome-coated metal, chrome-coated plastic and painted plastic
- Pressure-sensitive acrylic adhesive removable up to six months. Please test for removability with your specific application surface
- Backed with a layflat 90 lb. moisture stable polycoated release liner ideal for sheet-form converting
- Excellent stayflat release liner properties for printing and converting

Ask about FLEXcon's wide variety of colored vinyls, brilliant metallic polyesters and eye-catching holographic vinyls for bumper stickers.



Classics Plus® 41076

PRODUCT DATA	VALUE	TEST METHOD
Physical Properties		
Thickness (Mils[microns])	Film	3.5 (89) +/- 10%
	Adhesive	0.6-0.7 (15-18) +/- 0.1 (3)
	Liner	6.9 (175) +/- 10%
Dimensional Stability (%)	MD	< .75
	TD	< .50
Chemical Resistance	Water	Good
	Gasoline	Fair
	Basic Cleaners	Good
	Toluene	Poor
Adhesion Properties		
Ultimate Peel from	Average	
	Oz/In	(N/m)
	Auto Glass	47 (517)
	Chrome-Coated Metal	25 (275)
	Chrome-Coated Plastic	44 (484)
	Glass	47 (517)
Painted Plastic	42 (462)	
Expected Shear		ASTM D 3654 Method A a. 1 hr. dwell b. 1 sq. in. surface c. 4 lb. load
Room Temp (hours)	10	
Tack (gm/sq cm)	190	ASTM D 2979
Expected Exterior Life	Two Years	
Service Temperature Range	-40°F to 176°F (-40°C to 80°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years when stored at 70°F (21°C) and 50% relative humidity	

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.

Last Modified On: 11/23/2015

