

High Temp

.004" (4.0 Mil) Roll Form Laminating Adhesive
with Flame-Retardant Adhesive

*Applications include:
Mounting & Bonding
Laminating*

*For more information on
FLEXcon's
pressure-sensitive film
solutions for Mounting &
Bonding, contact your local
Sales Representative or our
Performance Products
Business Team at (508)
885-8440.*

Product ID #: FLX068879



Product:

**Flexcon®
FlexMount® L-59FR 068879
(4.0 Mil Transfer Tape,
Double 50# Liner)**

Benefits:

- 4.0 mil white flame-retardant non-halogenated adhesive
- Adhesive adheres well to acrylic, polypropylene, stainless steel, polyethylene, and glass
- Product is ideal for smooth surfaces applications
- Backed with two 50 lb. semi-bleached white kraft release liners ideal for roll-to-roll converting
- FlexMount® L-59FR products at a 2.0 mil to 4.0 mil adhesive thickness are rated UL 94 V-0 when bonded to 2.0 mil polyimide and 2.0 mil aluminum foil (UL E518655)



Flexcon®
FlexMount® L-59FR 068879
(4.0 Mil Transfer Tape,
Double 50# Liner)

PRODUCT DATA	VALUE	TEST METHOD
Physical Properties		
Thickness (Mils[microns])	50K-6	3.1 (79) +/- 10%
	Adhesive	3.9-4.1 (99-104) +/- 0.1 (3)
	Spec 50K-9	3.1 (79) +/- 10%
Expected Shear		ASTM D 3654 Method A a. 1 hr. dwell b. 1 sq. in. surface c. 4 lb. load
Room Temp (hours)	100	
Flammability	See other side for information	
Expected Exterior Life	Depends on substrates, adhesive is suitable for outdoor use	
Service Temperature Range	-40°F to 302°F (-40°C to 150°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years when stored at 70°F (21°C) and 50% relative humidity	

For guidance only - the data are based on three or less production runs.

[For the Complete Product Data View Featuring ASTM D 3330 Adhesion Results](#)

DISCLAIMER: FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE. This product is a device component intended solely for further processing, manufacturing, or incorporation into a finished device. Customer is solely responsible for determining whether this component product is fit for Customer's intended use, including, without limitation, incorporation into Customer's finished device(s), and for performing any additional testing that may be necessary to support Customer's intended use. Customer is solely responsible for ensuring that its use of the component product is in compliance with the applicable laws and for obtaining any necessary clearances or approvals from its use of the component product and any finished device that incorporates the component product. Full flame-retardant test results are available upon request.

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.
 Last Modified On: 09/17/2024

