

Transfer Tape

Single Liner

Pressure-sensitive transfer tape adhesives are the ideal solution for mounting and bonding because they transfer easily and bond well to many challenging surfaces.

Markets Include:

*Aerospace
Appliance
Automotive
Consumer Electronics
Durable Goods
Heavy Equipment
Industrial Equipment
Rail*

Applications Include:

*Nameplate/ Brand ID
Overlay
Decal
Sealing gaskets
Gap filling
Surface protection
Grip, traction and anti-slip
Noise and vibration control
Bonding films to replace rivets
and welds*

For more information on FLEXcon's pressure-sensitive film solutions for Transfer Tapes, contact your local Sales Representative or our Performance Products Business Team at (508) 885-8440.

Product ID #: FLX000564



Product: **FLEXcon® FLEXmount® TT
400 L-606 84 LA PFT**

Benefits:

- Permanent acrylic adhesive offers medium tack, high shear and excellent adhesion to a variety of metal and plastic surfaces, including polypropylene, polyethylene, PORON® and Kushon® cellular rubber products
- Adhesive exhibits exceptional performance on textured and uneven surfaces
- Backed with an 84 lb. natural kraft polycoated layflat differential release liner
- Heavy release liner has excellent moisture stability and is a good base for flatbed and steel rule diecutting
- Product is ideal for rough or textured surface applications
- Product is available in rolls
- UL recognized under UL 969 - UL File No. PGGU2.MH10170 Marking and Labeling System Materials - Component

FLEXcon® FLEXmount® TT 400 L-606 84 LA PFT

PRODUCT DATA	VALUE	TEST METHOD
Physical Properties		
Thickness (Mils[microns])	Adhesive 3.9-4.1 (99-104) +/- 0.2 (5) 84 LA PFT 6.4 (163) +/- 10%	ASTM D 3652 (Modified for use with non-tape products)
Expected Shear		ASTM D 3654 Method A a. 1 hr. dwell b. 1 sq. in. surface c. 4 lb. load
Room Temp (hours)	40	
Tack (gm/sq cm)	1710	ASTM D 2979
Expected Exterior Life	Dependant on life of substrate - suitable for outdoor use	
Service Temperature Range	-40°F to 302°F (-40°C to 150°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years when stored at 70°F (21°C) and 50% relative humidity	

For the Complete Product Data View: [FLEXmount® L-606/V-606 Adhesive Series Data Sheet](#)

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of Flexcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Flexcon. All purchasers of Flexcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Flexcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.

Last Modified On: 02/06/2024

