

Mounting Film

Clear Permanent/Removable

Mounting films promote easy application and excellent adhesion to a variety of surfaces for reliable and durable graphic attachments.

Markets Include:

*Aerospace
Appliance
Automotive
Consumer Electronics
Durable Goods
Heavy Equipment
Industrial Equipment
Promotional Advertising*

Applications Include:

*Counter Graphics
Display Graphics
Floor graphics
Nameplates
Tradeshow graphics
Window Graphics*

For more information on FLEXcon's pressure-sensitive film solutions for Mounting Films, contact your local Sales Representative or our Performance Products Business Team at (508) 885-8440.

Product ID #: FLX000526



Product: FLEXcon® FLEXmount® DFM 100 Clear
V-29 100 Poly H-9 V-133 150 Poly Blue

Benefits:

- 1.0 mil double-faced clear polyester film mounting film coated with a permanent pressure-sensitive acrylic adhesive on one side and a removable pressure-sensitive adhesive on the other side
- V-29 bonds well to printed base film surfaces
- Removable pressure-sensitive acrylic adhesive bonds well to metal, glass and high-surface energy plastics
- Ultra-smooth polyester release liner provides ultimate smoothness and flow-out of adhesive on the overlaminating film

FLEXcon® FLEXmount® DFM 100 Clear V-29 100 Poly H-9 V-133 150 Poly Blue

PRODUCT DATA	VALUE	TEST METHOD
Physical Properties		
Thickness (Mils[microns])	Film	1.0 (25) +/- 10%
	Liner	1.0 (25) +/- 5 %
	Adhesive	0.9-1.0 (23-25) +/- 0.1 (3)
	Liner	1.4 (36) +/- 5%
	Adhesive	0.7-0.8 (18-20) +/- 10%
	Liner	1.4 (36) +/- 5%
Expected Exterior Life	Depends on substrate; both adhesives are suitable for outdoor use	
Service Temperature Range	-20°F to 302°F (-29°C to 150°C)	
Minimum Application Temperature	50°F (10°C)	
Storage Stability	Two years when stored at 70°F (21°F) and 50% relative humidity	

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of Flexcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by Flexcon. All purchasers of Flexcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of Flexcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.

Last Modified On: 09/17/2019

